


SPIRAL

POLISHING PADS

DIAMOND PADS FOR
FLOOR POLISHING



SETTING NEW
STANDARDS



**HYPER
GRINDER**



GRIT AVAILABLE
FROM 60 TO 5000

HYPER FLEXIBLE
HYPER PERFORMANCE
HYPER RESISTENCE



SPIRAL FLOOR PADS



For **POLISHING CONCRETE**, concrete and self-leveling concrete coatings (such as Ultratop or Pandomo).

Restoring and **POLISHING OF MARBLE, TERRAZZO and NATURAL STONES.**

Thanks to the new design and the flexible and resistant support, SPIRAL quickly works to leave a smooth and polished finish.

To be used on dry concrete surfaces or with water on natural stone, marble and terrazzo. **The new flexible diamond SPIRAL discs are designed to obtain an incredibly shiny and scratch-free surface on marble, terrazzo and natural stones.**

SPIRAL is ideal for obtaining a semi-gloss, satin or opaque finish on trowelled concrete without exposure of the aggregate. SPIRAL is the best solution for preparing concrete before using intensifiers and sealants.

GUIDELINES FOR USE:

DRY polishing of trowelled concrete floors and self-leveling concrete coatings:

1. Start sanding with **SPIRAL 00** or **SPIRAL 0** according to the concrete conditions.
2. Apply **Concrete Hardener** for densification and wait for the product to dry.
3. When Concrete Hardener is completely dry use **SPIRAL 2**.

• **To obtain the different finishes, follow the instructions below:**

- A. **MATT FINISH:** apply **Concrete Shield Plus**.
- B. **SEMI-SHINY FINISH:** use **SPIRAL 3** and then apply **Concrete Shield Plus**.
- C. **SHINY FINISH:** use **SPIRAL 3** and 4 and then apply **Concrete Guard Lithium**.

• **For daily cleaning of treated floors** such as at points A and B in high traffic areas, use the **HyperClean** floor-cleaning pad. The use of chemicals is not required, the use of water is sufficient.

• **For the daily cleaning of floors treated** as in point C in high traffic areas, use a high speed monobrush.



WET polishing for marble, terrazzo and natural stone floors:

1. Depending on the surface conditions, start sanding with **SPIRAL 00** or **SPIRAL 0** to remove scratches.
2. Smooth the surface with **SPIRAL 1, 2, and 3**.
3. Polish with **Polish HG92** or, if mechanical polishing is to be avoided, use **SPIRAL 4** with water only.
4. Wash the surface with **Stone Sealer & Soap**.

• **For daily cleaning and maintenance** in high traffic areas use the **HyperClean** floor-wash and Stone Sealer & Soap pad.



SPIRAL DISKS ARE AVAILABLE IN ALL SIZES FOR MONO-BRUSH AND FLOOR GRINDERS

Model	GRIT	Description
SPIRAL 000	60	Very aggressive grit to remove large scratches and marks on helical concrete surfaces or natural stones.
SPIRAL 00	120	To remove large scratches and marks on trowelled concrete surfaces or natural stones.
SPIRAL 0	220	Recommended for the removal of light marks on trowelled concrete and scratches on natural stones. Leave the concrete surface in ideal conditions for the use of the densifier Concrete Hardener.
SPIRAL 1	400	To be used after SPIRAL 0. Removes excess densifier or Concrete Hardener leaving a matte finish. It removes marks and small scratches from the natural stone surface.
SPIRAL 2	800	To be used after SPIRAL 1. For a satin finish.
SPIRAL 3	1500	To be used after SPIRAL 2. For a semi-gloss finish.
SPIRAL 4	3000	To be used after SPIRAL 3. For a glossy finish.
SPIRAL 4	5000	To be used after SPIRAL 4. Maximum polishing and mechanical brilliance.



ADVANTAGES:

- ✓ **No “orange peel” effect:** SPIRAL pads prevent the formation of the “orange peel” effect even on softer stones.
- ✓ **Faster polishing:** SPIRAL pads require fewer steps than traditional maintenance pads.
- ✓ **Higher gloss and shine levels:** better performance than traditional pads.
- ✓ **Wide range of GRITs:** available from GRIT 60 to GRIT 5000.
- ✓ **Wide range of sizes:** available in sizes from 4 “to 21” for all floor grinding and polishing machines.
- ✓ **Great flexibility:** they follow perfectly the undulations and the unevenness of the surface.
- ✓ **Wet & Dry system.**



4" SPIRAL FLOOR PAD - Ø 100MM

HG1040	SPIRAL 000	grit 60
HG1041	SPIRAL 00	grit 120
HG1042	SPIRAL 0	grit 220
HG1043	SPIRAL 1	grit 400
HG1044	SPIRAL 2	grit 800
HG1045	SPIRAL 3	grit 1500
HG1046	SPIRAL 4	grit 3000
HG1047	SPIRAL 5	grit 5000

8" SPIRAL FLOOR PAD - Ø 200MM

HG1079	SPIRAL 000	grit 60
HG1080	SPIRAL 00	grit 120
HG1081	SPIRAL 0	grit 220
HG1082	SPIRAL 1	grit 400
HG1083	SPIRAL 2	grit 800
HG1084	SPIRAL 3	grit 1500
HG1085	SPIRAL 4	grit 3000
HG1085	SPIRAL 5	grit 5000

13" SPIRAL FLOOR PAD - Ø 330MM

HG1128	SPIRAL 000	grit 60
HG1129	SPIRAL 00	grit 120
HG1130	SPIRAL 0	grit 220
HG1131	SPIRAL 1	grit 400
HG1132	SPIRAL 2	grit 800
HG1133	SPIRAL 3	grit 1500
HG1134	SPIRAL 4	grit 3000
HG1135	SPIRAL 5	grit 5000

17" SPIRAL FLOOR PAD - Ø 430MM

HG1168	SPIRAL 000	grit 60
HG1169	SPIRAL 00	grit 120
HG1170	SPIRAL 0	grit 220
HG1171	SPIRAL 1	grit 400
HG1172	SPIRAL 2	grit 800
HG1173	SPIRAL 3	grit 1500
HG1174	SPIRAL 4	grit 3000
HG1173	SPIRAL 5	grit 5000

20" SPIRAL FLOOR PAD - Ø 500MM

HG1198	SPIRAL 000	grit 60
HG1199	SPIRAL 00	grit 120
HG1200	SPIRAL 0	grit 220
HG1201	SPIRAL 1	grit 400
HG1202	SPIRAL 2	grit 800
HG1203	SPIRAL 3	grit 1500
HG1204	SPIRAL 4	grit 3000
HG1203	SPIRAL 5	grit 5000

5,5" SPIRAL FLOOR PAD - Ø 140MM

HG1498	SPIRAL 000	grit 60
HG1499	SPIRAL 00	grit 120
HG1500	SPIRAL 0	grit 220
HG1501	SPIRAL 1	grit 400
HG1502	SPIRAL 2	grit 800
HG1503	SPIRAL 3	grit 1500
HG1504	SPIRAL 4	grit 3000
HG1505	SPIRAL 3	grit 5000

9,5" SPIRAL FLOOR PAD - Ø 240MM

HG1088	SPIRAL 000	grit 60
HG1088	SPIRAL 00	grit 120
HG1090	SPIRAL 0	grit 220
HG1091	SPIRAL 1	grit 400
HG1092	SPIRAL 2	grit 800
HG1093	SPIRAL 3	grit 1500
HG1094	SPIRAL 4	grit 3000
HG1095	SPIRAL 5	grit 5000

16" SPIRAL FLOOR PAD - Ø 410MM

HG1158	SPIRAL 000	grit 60
HG1159	SPIRAL 00	grit 120
HG11HG	SPIRAL 0	grit 220
HG1161	SPIRAL 1	grit 400
HG1162	SPIRAL 2	grit 800
HG1163	SPIRAL 3	grit 1500
HG1164	SPIRAL 4	grit 3000
HG1163	SPIRAL 3	grit 5000

18" SPIRAL FLOOR PAD - Ø 450MM

HG1178	SPIRAL 000	grit 60
HG1179	SPIRAL 00	grit 120
HG1180	SPIRAL 0	grit 220
HG1181	SPIRAL 1	grit 400
HG1182	SPIRAL 2	grit 800
HG1183	SPIRAL 3	grit 1500
HG1184	SPIRAL 4	grit 3000
HG1183	SPIRAL 5	grit 1500

26" SPIRAL FLOOR PAD - Ø 660MM

HG12HG	SPIRAL 000	grit 60
HG1261	SPIRAL 00	grit 120
HG1262	SPIRAL 0	grit 220
HG1263	SPIRAL 1	grit 400
HG1264	SPIRAL 2	grit 800
HG1265	SPIRAL 3	grit 1500
HG1266	SPIRAL 4	grit 3000
HG1265	SPIRAL 5	grit 1500

**HG HYPER GRINDER S.R.L**

Via Chieti, 6 | 65121 Pescara (PE) | ITALY

P.Iva 02223280682 | hypergrinder@pec.it | Tel +39 085 921 8160www.hypergrinder.com | info@hypergrinder.com

Your Distributor:



rev.11092019